



## aegex10™ intrinsically safe tablet

**Aegex Technologies provides intrinsically safe solutions for the world's most hazardous industrial operations in oil and gas, chemical, mining, pharmaceutical, public safety, utilities and other industries with explosive environments.** Aegex solutions bring real-time connectivity to hazardous areas, helping organizations harness the power of data to optimize efficiency, safety and productivity.



Oil & Gas



Chemical



Mining



Pharmaceutical



Public Safety



Utilities

The **aegex10™ Intrinsically Safe Tablet** is the most advanced, efficient, lightweight and rugged Windows tablet that is purpose-built for **Zone 1 / Division 1 hazardous areas**. Simple to deploy, it is the basis for an Industrial Internet of Things platform for hazardous industries, allowing operations to easily begin their digital transformation to Industry 4.0.

### ◆ Purpose-Built Intrinsically Safe and Enterprise-Class Tablets:

Aegex devices are certified ATEX/IECEX Zone 1; certified by SGS to UL 913 Class I, II, III Division 1 Groups A-G; and IP65 for hazardous (classified) locations.

### ◆ Solutions for All Hazardous Zones and Jobs:

Aegex devices run the operating system and applications that allows for secure enterprise deployments.

### ◆ Enterprise Collaboration

Aegex devices use 4G LTE or Wi-Fi for real-time communications.



Certified ATEX/IECEX Zone 1

Certified by SGS to  
UL 913 C I, II, III Div 1

10.1" WUXGA Display

Powered by Intel  
Atom Quad Core

Windows 10



**ExLoc**  
INSTRUMENTS

SALES@EXLOC.COM



# SPECIFICATIONS

## Intrinsically Safe Certifications

UL913 5<sup>th</sup> edition:  
 C I, II, III Div 1 Gr A-G T4, T<sub>amb</sub> = -10°C...+50°C  
 CI Z0 Gr IIC T4 IP65, T<sub>amb</sub> = -10°C...+50°C  
 CAN/CSA-22.2 Part 157

IECEX 60079-0 & -11:  
 Ex ib IIC T6 Gb, T<sub>amb</sub> = -10°C...+50°C  
 Ex ib IIIC T85°C Db IP6X, T<sub>amb</sub> = -10°C...+50°C  
 Ex ib I Mb, Tamb = -10°C...+50°C

ATEX 60079-0 & -11:  
 Ⓜ II 2G Ex ib IIC T6 Gb, T<sub>amb</sub> = -10°C...+50°C  
 Ⓜ II 2D Ex ib IIIC T85°C Db IP6X, T<sub>amb</sub> = -10°C...+50°C  
 Ⓜ I M2 Ex ib I Mb, Tamb = -10°C...+50°C

<b>Exterior</b>	Dimensions: 273 x 185 x 16.8 mm (10.75 x 7.28 x 0.66 in) Weight: 980 grams (2.16 lbs) IP65
<b>Display</b>	Screen: 10.1" AHVA Full HD Plus Resolution: 1920 x 1200 Capacitive touch: Multi-touch Contrast 800:1 Viewing angle (up/down, left/right) 170°
<b>Battery Life</b>	Up to 12 hours of web browsing (Battery: 3.8V, 8700mAh, 33Wh)
<b>Charging time</b> (in standby)	Docking station: 0-90% in 2.5hours, to 100% in approx. 3.5 hours USB charger: 0-90% in 4hours, to 100% in approx. 5.5 hours
<b>Storage/RAM</b>	128GB storage / 4GB RAM
<b>CPU &amp; Wireless</b>	Intel® Quad-Core Atom processor 2.39GHz*, 4G LTE available Wi-Fi 802.11 a/b/g/n dual band Bluetooth® 4.0 Low Energy technology NFC Intel Wireless Display
	<p><b>* LTE (EU, US, AU): Telit LN940A9</b>          - LTE: Band 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 18, 19, 20, 21, 25, 26, 28, 29, 30, 38, 39, 40, 41, 66          - WCDMA: Band 1, 2, 3, 4, 5, 6, 8, 19          - GSM/GPRS/EDGE: N/A</p> <p><b>LTE (North America): Sierra EM7355</b>          - LTE: FDD Band 2,4,5,13,17,25 all bands with diversity          - UMTS/HSPA+: Band 1,2,4,5,8, all bands with diversity          - CDMA 1xRTT/EV-DO Rev A: BC0, BC1, BC10          - GSM/GPRS/EDGE: Quad-Band</p> <p><b>LTE (international): Huawei ME936</b>          - LTE: FDD Band 1,2,3,4,5,7,8,13,17,20, all bands with diversity          - WCDMA/HSDPA/HSUPA/HSPA+: Band 1,2,4,5,8, all bands with diversity          - GSM/GPRS/EDGE: 850/900/1800/1900MHz</p>
<b>Location</b>	GPS / GLONASS (cold start <30s, warm start < 5s)
<b>Ports</b>	Full-size USB 2.0 USB 3.0, Ethernet, and HDMI on system connector Micro USB for charging Charging pads (12V) microSDXC™ card slot (supports up to 2TB) Headset jack
<b>Software</b>	Windows 10 IoT Enterprise
<b>Cameras, Video &amp; Audio</b>	8.0 megapixel autofocus rear-facing camera with flash, full HD video 2.0 megapixel front-facing camera full HD video Front and rear microphones Stereo speakers
<b>Sensors</b>	Ambient light sensor, Accelerometer, Gyroscope, E-Compass, SAR proximity sensor
<b>Security</b>	Silicon Level, Intel Security (SMER, PPDRNG, fTPM, and TPM 2.0) Software Level Device Control Windows 10 Mobile Device Management BitLocker

**In the box** aegex10™ intrinsically safe tablet  
 Wall charger (power supply + USB cable)



To request a demo or to talk to a product specialist, please contact our nearest office or go to:

[WWW.EXLOC.COM](http://WWW.EXLOC.COM)

**HEADQUARTERS**  
 Exloc Instruments Inc.  
 15584 Summit Park Dr.  
 Suite 303  
 Montgomery, TX 77356  
 (281) 978-2040

**UK OFFICE**  
 Exloc Instruments UK Ltd.  
 Unit 7  
 Riverside Court  
 Delph, OL3 5F3, U.K.  
 +44 (0) 1457-239301



\*Base Frequency 1.59 GHz, Burst Frequency 2.39 GHz  
 \*Subject to verification of local carrier requirements  
 \*\*P2P: ISO 18092, Reader/Writer: ISO 14443 -A-B, MIFARE, FelCa®, ISO 15693, NFC Forum Tag Types 1 to 4  
 Card emulation: ISO 14443 -A-B-B', MIFARE, FelCa RF, Distance up to 3 cm