

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification System for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX EPS 19.0111X

Page 1 of 5

Certificate history: Issue 0 (2019-11-19)

Status:

Current

Issue No: 1

Date of Issue:

2020-02-25

Applicant:

BEx-Solution GmbH Lange Straße 99

76199 Karlsruhe Germany

Equipment:

BEx2-Remote IO, Type 24*****

Optional accessory:

Type of Protection:

ec, ia, mc

Marking:

Ex ec mc [ia Ga] IIC T4 Gc

[Ex ia Da] IIIC

Approved for issue on behalf of the IECEx Certification Body:

Position:

Signature:

(for printed version)

Date:

Holger Schaffer

Certification Manager

2020-02-25

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.

Certificate issued by:

Bureau Veritas Consumer Products Services Germany GmbH **Businesspark A96** 86842 Türkheim Germany





IECEx Certificate of Conformity

Certificate No.:

IECEX EPS 19.0111X

Page 2 of 5

Date of issue:

2020-02-25

Issue No: 1

Manufacturer:

BEx-Solution GmbH Lange Straße 99 76199 Karlsruhe Germany

Additional manufacturing locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017

Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

Edition:6.0

IEC 60079-18:2017 Expl

Explosive atmospheres - Part 18: Protection by encapsulation "m"

Edition:4.1

Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

Edition:5.1

IEC 60079-7:2017

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

DE/EPS/ExTR19.0114/01

Quality Assessment Report:

DE/PTZ/QAR18.0002/01



IECEx Certificate of Conformity

Certificate No.:

IECEX EPS 19.0111X

Page 3 of 5

Date of issue:

2020-02-25

Issue No: 1

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The equipment is a Remote IO system which isolates the non-intrinsically safe input circuits and the supply circuits from the intrinsically safe output circuits. It provides a transfer of non-intrinsically safe input signals to intrinsically safe output signals. The input circuits are suitable to be located in zone 2 (EPL Gc) and the output circuits are suitable to be connected to other intrinsically safe circuits in zone 0 (EPL Ga). The equipment is also suitable to be located outside a hazardous area and the output circuits to be connected to other intrinsically safe circuits in zone 20 (EPL Da). The Remote IO system includes a variety of different modules, differing in the bus type to be connected. The equipment has to be installed in a suitable housing (see special conditions).

SPECIFIC CONDITIONS OF USE: YES as shown below:

The BEx2-Remote IO of the types 2420010*, 2420020*, 2420030*, 2420040*, 2420050* and 2420060* have to be installed in a suitable housing according to the directive 2014/34/EU and the IECEx-Scheme in such a way, that a degree of protection of at least IP 54 is reached.

The non-intrinsically safe terminals of the equipment (terminals X9 and X10) shall be supplied by a source providing SELV output circuit or conforming to IEC 61010 or IEC 60950 (Um=30V DC).



IECEX Certificate of Conformity

Certificate No.:

IECEX EPS 19.0111X

Page 4 of 5

Date of issue:

2020-02-25

Issue No: 1

Equipment (continued):

Electrical data:

U_m = 30 V DC

(Terminals X9 / X10)

Terminal block X1 to X8 (output parameters of each clamp, clamps are not allowed to be combined):

Clamp (26 V):

 $U_0 = 26 \text{ V d.c.}$

 $I_0 = 82 \text{ mA}$

 $P_0 = 533 \text{ mW}$

		Group IIC		
Lo	3 mH	1 mH	0.5 mH	0 mH
Co	42 nF	62 nF	78 nF	99 nF
		Group IIB / III		
Lo	20 mH	2 mH	0.5 mH	0 mH
Co	350 nF	350 nF	490 nF	770 nF

Clamp (9.6 V)

 $U_0 = 9.6 \text{ V d.c.}$

 $I_0 = 31 \text{ mA}$

 $P_0 = 75 \text{ mW}$

		Group IIC		
Lo	49 mH	10 mH	1 mH	0 mH
Co	310 nF	640 nF	1.1 µF	3.6 µF
		Group IIB / III		
Lo	100 mH	10 mH	1 mH	0 mH
Co	2 µF	3.6 µF	6.1 µF	26 µF

Clamp (GND):

Galvanically separated from input GND

	Type: 24200*00	Type: 24200*01	Type: 24500*02
Clamp 1	$U_0 = 26 \text{ V d.c.}$	$U_0 = 26 \text{ V d.c.}$	$U_0 = 9.6 \text{ V d.c.}$
Clamp 2	GND	GND	GND
Clamp 3	U _o = 26 V d.c.	U _o = 9.6 V d.c.	$U_0 = 9.6 \text{ V d.c.}$
Clamp 4	GND	GND	GND
Clamp 5	U _o = 9.6 V d.c.	U _o = 9.6 V d.c.	U _o = 9.6 V d.c.
Clamp 6	GND	GND	GND
Clamp 7	U _o = 26 V d.c.	U _o = 26 V d.c.	U _o = 9.6 V d.c.
Clamp 8	GND	GND	GND



IECEx Certificate of Conformity

Certificate No.:

IECEX EPS 19.0111X

Page 5 of 5

Date of issue:

2020-02-25

Issue No: 1

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Adding further variants.