

The mobile multifunctional set consisting of a Trigger Handle (hand-held barcode scanner) and an industrial smartphone IS530.x is a flexible combination for reliable data acquisition in Ex areas. The HID-active, ready-to-use high-performance scanner captures any 1D or 2D barcodes at close range of up to 6 meters or distances of over 15 meters via the reliable Zebra OEM imager scan engines. The data is further processed directly via the IS530.x smartphone connected via the ISM interface.

<sup>)</sup> All trademarks and copyrights are the properties of their respective owners. ) © 2022 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1040MD01REV11\_EN\_01.2022





(IS-TH1xx.1)



ATEX approval: Ex-Zone 1/21 Il 2G Ex ib op is IIC T4 Gb Il 2D Ex ib op is IIIC T135°C Db



IECEx approval: Ex-Zone 1/21 Ex ib op is IIC T4 Gb Ex ib op is IIIC T135°C Db



NEC500 approval:

Class I Division 1, Groups A B C D T4 Class II Division 1, Groups E F G T135°C Class III Division 1

Further approvals: JNIOSH (Japan)

## TECHNICAL FEATURES

**Weight** MR =  $380 \text{ g} \mid \text{ER} = 400 \text{ g} \text{ (without IS530)}$ 

**Size** 200 x 125 x 82 mm

**Indication function** Loudspeaker | Vibration | LED-Display

**Power supply** Over IS530 | this can be loaded in the handle

**Communication** Over the multi functional ISM interface of the IS530

Type of protection MIL-STD 810G | IP68

## **SCAN TYPES**

- IS-TH1MR.1 (mid range) with Zebra SE4750 MR | up to 6 m
- IS-TH1ER.1 (extended range) with Zebra SE4850 ER | over 15 m



\ IS530.1 \



Android<sup>™</sup> 10



4,5" Gorilla Glass®
3. generation,
resolution 854 x 480 pixels



3600 mAh battery, replaceable, 3.8 V. 13.68 Wh



Bluetooth® 5



GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 LTE-TDD: B38/B39/B40/B41 TD-5CDMA: B34/B39



Qualcomm Snapdragon SDM660 Octa-Core Kryo Gold-Quad cores 2,2 GHz Kryo Silver-Quad cores 1,8 GHz 4 GB RAM 64 GB internal memory



2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with hotspot for max. 8 connections

The complete description you will find on our homepage: www.isafe-mobile.com