



SSG Industrial LiFePO₄ UPS, 1.5 to 3kVA

Lithium Iron Phosphate Battery



LiFePO₄ UPS Advantages:

- **Very lightweight – 44% less**
Each Falcon LiFePO₄ battery pack weighs 44% less than a lead-acid equivalent. This is ideal for applications with a weight/footprint requirement.
- **3 to 4 times longer runtimes**
The high-energy battery capacity means *fewer battery packs* and longer runtimes.
- **Long service life: 10-years plus**
With 4 times more charge/discharge cycles, you cut battery replacements and service costs.
- **-20°C to 55°C temperature range**
Tolerance of wide temperatures makes the SSG Industrial LiFePO₄ UPS ideal for demanding environments.
- **Advanced safety**
Lithium iron cathode material has no thermal runaway issues. The LiFePO₄ battery is safe for the environment. It has no caustic materials or dangerous odors.
- **Falcon is recognized for quality and reliability**
Falcon Electric is a recognized authority in industrial UPS solutions. Our technical expertise assures you find the right solution—the first time.

Model Number	SSG1.5KRM-1 SSG1.5KRM-2	SSG2.2KRM-1 SSG2.2KRM-2	SSG3KRM-1 SSG3KRM-2
Nominal VA	1500	2200	3000
Electrical Input			
Nominal AC Voltage	-1 Models: 120Vac, -2 Models: 208, 220, 230, 240Vac		
AC Voltage Range	-1 Models: 80-138Vac, -2 Models: 160-276Vac		
Frequency	50/60 Hz ± 5% (Auto Tracking)		
Power Factor Correction	>0.97 (at full load)		
Surge Suppression	IEEE/ANSI C62.41		
Efficiency (Typ.)	88%		
Electrical Output			
Watts	1050	1540	2100
AC Voltage (User Programmable)	-1 Models: 100, 110, 115 or 120Vac (sine wave) -2 Models: 208, 220, 230 or 240Vac (sine wave)		
Frequency	50/60 Hz (Auto Tracking)		
Frequency Stability	± 0.3% (Battery Mode), ± 5% Synchronized to the input frequency in utility mode		
Voltage Regulation	± 2%		
Step Load Change	± 7% for 100% load variation, recovery in 5ms		
Harmonic Distortion	< 3% Linear Load, < 5% Non-Linear Load		
Overload	110% for 40 seconds, 125% for 18 seconds, 150% immediate		
Crest Ratio	3:1		
Battery			
DC Bus Voltage (nominal)	48Vdc	96Vdc	
Battery Pack Type	User-Replaceable, Hot-Swappable Pack Separate Enclosure from UPS Module (Internal Pack for 1.5kVA)		
Battery Type	10-Year Plus Rated, 51.2V Battery Pack		
Battery Runtimes	20 / 42 / 96	29 / 61 / 139	20 / 42 / 96
Full/Half/Quarter Load in Minutes			
Recharge Time	11 Hours to 90%		
Transfer Time			
Line Fails/Recovers	Zero		
UPS to Bypass or Reverse	< 4ms		
After Overload	Auto Transfer to UPS		
Electrical Connections - For hardwired models, contact factory.			
Input	-1 6' Cord with 5-15P Plug -2 6' Cord with Schuko Plug	6' Cord with 5-20P Plug 6' Cord with Schuko Plug	6' Cord with L5-30P Plug 6' Cord with Schuko Plug
Output	-1 (8) 5-15R -2 (4) IEC320 C13 Outlets	(4) 5-15R & (1) L5-20R (4) IEC320 C13 Outlets	(4) 5-15R & (1) L5-30R (4) IEC320 C13 Outlets
Environmental			
Temperature	Operational Storage	-20°C to 55°C (-4°F to 131°F) -20°C to 55°C (-4°F to 131°F)	
Humidity		10% to 95% Non – Condensing	
Altitude		10,000 Feet (3,000 meters) without derating	
Cooling		Low Velocity Forced Air Fans	
Heat Dissipation	BTU/Hour	535	784
Audible Noise	(@ 1 Meter)	<50dBA	
Controls & Indicators			
LCD Display	MIMIC Graphical Display, Input/Output Voltage, Frequency, Load, Alarm, Programmable settings & UPS state icons		
Audible Alarms	DC Mode, Low Battery, Over/Under Voltage, Over/Under Frequency, High Temp., Overload, Fault Alarm		
Load Segment Control	Two programmable load segments, one continuous load segment (Except on -2 models)		
Remote Emergency Power Off (or)	(Standard)	Meets NFPA 70, NEC 645-11 (REPO connections located on the UPS rear panel)	
Remote Output Receptacle Control	(Optional)	UPS Load Segment Controlled Output Receptacles can be turned off and on using a remote isolated switch contact.	
Communications	USB Port, RS-232C Serial Port, Optional SNMP/HTTP Agent Board (UPS Bundled UPSilon Software)		
Mechanical - For mounting dimensions, contact factory.			
UPS Dimensions H x W x D	inches (mm)	(2U) 3.5 x 19 x 22.5 (88.9 x 482.6 x 571.5) (None - Batteries inside UPS)	(2U) 3.5 x 19 x 21.9 (88.9 x 482.6 x 556.3) (2U) 3.5 x 19 x 21.3 (88.9 x 482.6 x 541)
SSGR Battery Module			
Weight	lb. (kg)	UPS with Internal batteries = 41 (18.6)	(2U) UPS Module = 32 (14.5) (2U) External Battery Module = 49 (22.2)

SSG UPS Options								
Extended Battery Bank Options – LiFePO ₄								
Extended Battery Bank Model Numbers		SSGR		SSGR-1	SSGR-2			
Battery Type		10-Year Plus Rated, 51.2V Battery Pack						
Temperature	Operational	-20°C to 55°C (-4°F to 131°F)						
	Storage	-20°C to 55°C (-4°F to 131°F)						
Internal 2A Charger		No		Yes				
Charger Input Voltage & Current		None		120Vac, 2.5A	208Vac to 240Vac, 2.5A			
Dimensions H x W x D		inches (mm)		(2U) 3.5 x 19 x 21.3 (88.9 x 482.6 x 541)				
Weight		lb. (kg)		Extended Battery Module = 41 (18.6)		Extended Battery Module = 49 (22.2)		
For mounting dimensions, contact factory.								
Extended Battery Runtimes – LiFePO ₄								
(Note: Stated battery runtimes are identical for SSGR, SSGR-1, SSGR-2 battery banks and are stated by UPS models below)								
UPS Model Numbers		SSG1.5KRM-1		SSG2.2KRM-1		SSG3KRM-1		
		SSG1.5KRM-2		SSG2.2KRM-2		SSG3KRM-2		
Battery Runtimes by Model		1050W / 525W / 262.5W		1540W / 770W / 385W		2100W / 1050W / 525W		
Full/Half/Quarter Load in Minutes								
UPS as Shipped		20 / 42 / 96		29 / 61 / 139		20 / 42 / 96		
One Extended Battery Bank		63 / 132 / 288		61 / 128 / 278		42 / 88 / 192		
Two Extended Battery Banks		105 / 220 / 480		N/A		N/A		
Three Extended Battery Banks		147 / 309 / 672		N/A		N/A		
Communications Options								
Internal COM Board Model Numbers		UA88376-SSG		UA88376-SSG-HW		SNMP-SG-4		SNMP-MEGA-INT
Type		Dry Relay Signal Interface			Ultra Secure SNMP/HTTP		Secure SNMP/HTTP	
COM Interface		DB-9F		Hardwire Terminal Block		10/100 Ethernet (RJ45)		
Communications Specifications		Dry contact for: Utility Loss, Low Battery, Summary Alarm & On Bypass, Remote Shutdown while on Battery			Internet-based remote UPS monitoring and management via SNMP/HTTP			
External COM Board Model Numbers					SNMP-SG-5		SNMP-MEGA-EXT	
COM Interface					10/100 Ethernet (RJ45)			
Communications Specifications					Internet-based remote UPS monitoring and management via SNMP/HTTP			

Typical SSG Rear Panel Configuration

